

SPEC. NO.: PS-51692-XXXXX-XXX

REVISION: JA

PRODUCT NAME: 0.4 mm PITCH ZIF BACK-FLIP FPC CONN.

SMT R/A D/C TYPE

PRODUCT NO: 51692 SERIES

PREPARED: DATE: 2016/10/05	CHECKED: DATE: 2016/10/05	APPROVED: DATE 2016/10/05
---------------------------------------------------------------	--------------------------------------------------------------	--------------------------------------------------------------

TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **2** OF **15**

1	REVISION HISTORY	3
2	SCOPE.....	4
3	APPLICABLE DOCUMENTS	4
4	REQUIREMENTS	4
5	PERFORMANCE	5
6	INFRARED REFLOW CONDITION.....	8
7	PRODUCT QUALIFICATION AND TEST SEQUENCE.....	9
8	CONNECTOR OPERATION	10

Aces P/N: **51692 series**

TITLE: **0.4 MM PITCH ZIF BACK-FLIP FPC CONN**

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **3** OF **15**

1 Revision History

Rev.	ECN #	Revision Description	Prepared	Date
O	ECN-1607346	ADD CONNECTOR OPERATION & RELEASE REV-O	JAMESLEN	2016.07.15
A	ECN-1610012	ADD Working voltage	JAMESLEN	2016.10.05

TITLE: **0.4 MM PITCH ZIF BACK-FLIP FPC CONN**

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **4** OF **15**

2 SCOPE

This specification covers performance, tests and quality requirements for 0.4 mm pitch 1.0 mm above board, Both contact, ZIF Back-Flip FPC connector.

ACES Part/Number : 51692-XXXXX-XXX

3 APPLICABLE DOCUMENTS

EIA-364: ELECTRONICS INDUSTRIES ASSOCIATION

4 REQUIREMENTS

4.1 Design and Construction

- 4.1.1 Product shall be of design, construction and physical dimensions specified on applicable product drawing.
- 4.1.2 All materials conform to R.o.H.S. and the standard depends on TQ-WI-140101.

4.2 Materials and Finish

- 4.2.1 Contact: High performance copper alloy (Phosphor Bronze)
Finish: (a) Contact Area: Refer to the drawing.
(b) Under plate: Refer to the drawing.
(c) Solder area: Refer to the drawing.
- 4.2.2 Housing: Thermoplastic or Thermoplastic High Temp., UL94V-0
- 4.2.3 Actuator: Thermoplastic or Thermoplastic High Temp., UL94V-0

4.3 Ratings

- 4.3.1 Working voltage less than 36 volts AC (per pin)
- 4.3.2 Voltage: 50 Volts AC (per pin)
- 4.3.3 Current: 0.3 Amperes (per pin)
- 4.3.4 Operating Temperature : -40°C to +85°C

TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **5** OF **15****5 Performance****5.1. Test Requirements and Procedures Summary**

Item	Requirement	Standard
Examination of Product	Product shall meet requirements of applicable product drawing and specification.	Visual, dimensional and functional per applicable quality inspection plan.
ELECTRICAL		
Item	Requirement	Standard
Low Level Contact Resistance	100 m Ω Max. per contact	Mate connectors, measure by dry circuit, 20mV Max., 100mA Max. (EIA-364-23)
Insulation Resistance	1000 M Ω Min.	Unmated connectors, apply 250 V DC between adjacent terminals. applied for 1 min. (EIA-364-21)
Dielectric Withstanding Voltage	No discharge, flashover or breakdown. Current leakage: 1 mA max.	250 VAC Min. at sea level for 1 minute. Test between adjacent contacts of unmated connectors. (EIA-364-20)
Temperature rise	30°C Max. Change allowed	Mate connector: measure the temperature rise at rated current until temperature stable. The ambient condition is still air at 25°C (EIA-364-70, METHOD1,CONDITION1)

TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **6** OF **15****MECHANICAL**

Item	Requirement	Standard
Durability	20 cycles.	The sample should be mounted in the tester and fully mated and unmated the number of cycles specified at the rate of 25.4 ± 3mm/min. (EIA-364-09)
FPC Retention Force	Min. 0.1N/pin contact X pin contacts(initial)	A connector shall be soldered on a board and insert the actuator, pull the FPC at the speed rate of 25.4 ± 3 mm/min.
Terminal /Housing Retention Force	30 gf MIN.	Operation Speed : 25.4 ± 3 mm/minute. Measure the contact retention force with Tensile strength tester.
Fitting Nail /Housing Retention Force	50 gf MIN.	Operation Speed : 25.4 ± 3 mm/minute. Measure the contact retention force with Tensile strength tester.
Vibration	1 μs Max.	The electrical load condition shall be 100 mA maximum for all contacts. Subject to a simple harmonic motion having amplitude of 0.76mm (1.52mm maximum total excursion) in frequency between the limits of 10 and 55 Hz. The entire frequency range, from 10 to 55 Hz and return to 10 Hz, shall be traversed in approximately 1 minute. This motion shall be applied for 2 hours in each of three mutually perpendicular directions. (EIA-364-28 Condition I)
Shock (Mechanical)	1 μs Max.	Subject mated connectors to 50 G's (peak value) half-sine shock pulses of 11 milliseconds duration. Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks). The electrical load condition shall be 100mA maximum for all contacts. (EIA-364-27, test condition A)

TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **7** OF **15****ENVIRONMENTAL**

Item	Requirement	Standard
Resistance to Reflow Soldering Heat	See Product Qualification and Test Sequence Group 9 (Lead Free)	Pre Heat : 150°C~180°C, 60~120sec. Heat : 230°C Min., 40sec Min. Peak Temp. : 260°C Max, 10sec Max.
Thermal Shok (with FPC mated)	See Product Qualification and Test Sequence Group 4	Mate module and subject to follow condition for 5 cycles. 1 cycles: -55 +0/-3 °C, 30 minutes +85 +3/-0 °C, 30 minutes (EIA-364-32, test condition I)
Humidity (with FPC mated)	See Product Qualification and Test Sequence Group 4	Mated Connector 40°C, 90~95% RH, 120 hours. (EIA-364-31, Condition A, Method II)
Temperature life (with FPC mated)	See Product Qualification and Test Sequence Group 5	Subject mated connectors to temperature life at 85°C for 96 hours. (EIA-364-17, Test condition A)
Salt Spray (with FPC mated) (Only For Gold Plating)	See Product Qualification and Test Sequence Group 6	Subject mated/unmated connectors to 5% salt-solution concentration, 35°C (I) Gold flash for 8 hours (II) Gold plating 3 u" for 48 hours (III) Gold plating 5 u" for 96 hours (EIA-364-26)
Solder ability	Tin plating: Solder able area shall have minimum of 95% solder coverage. Gold plating: Solder able area shall have minimum of 75% solder coverage	And then into solder bath, Temperature at 245 ±5°C, for 4-5 sec. (EIA-364-52)
Hand Soldering Temperature Resistance	Appearance: No damage Sequence Group 10	T ≥ 300°C, 5sec at least. T ≥ 350°C, 3sec at least.

Note. Flowing Mixed Gas shall be conduct by customer request.

TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN


RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **8** OF **15**

6 INFRARED REFLOW CONDITION



TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **9** OF **15****7 PRODUCT QUALIFICATION AND TEST SEQUENCE**

Test or Examination	Test Group									
	1	2	3	4	5	6	7	8	9	10
	Test Sequence									
Examination of Product				1、7	1、6	1、4		1	1	1
Low Level Contact Resistance		1、5	1、4	2、10	2、9	2、5			3	
Insulation Resistance				3、9	3、8					
Dielectric Withstanding Voltage				4、8	4、7					
Temperature rise	1									
Durability		3								
Vibration			2							
Shock (Mechanical)			3							
Thermal Shock				5						
Humidity				6						
Temperature life					5					
Salt Spray(Only For Gold Plating)						3				
Solder ability							1			
FPC Retention Force		2、4								
Terminal / Housing Retention Force										2
Fitting Nail /Housing Retention Force										3
Resistance to Soldering Heat									2	
Hand Soldering Temperature Resistance								2		
Sample Size	2	4	4	4	4	4	2	4	4	4

TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05



REVISION: A

ECN No: ECN-1610012

PAGE: **10** OF **15****8 CONNECTOR OPERATION**

Exercise care when handling connectors. Follow recommendations given below.

- A. Please open and close the actuator with the connector is mounted on the P.C.Board, and the FPC inserted. The actuator might not come off from the opening and shutting of the actuator in the state that FPC is not inserted and do not do, please.
- B. FPC Correct insertion verification
A visual comparison of the edge of the housing opening and the FPC pattern boundary will prevent diagonal insertion and partial insertion errors.



TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN



RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **11** OF **15****C. Locking**

After FPC/FFC insertion, rotate the actuator down to a full stop, pushing it at the center.



About the lock operation When you lock, it is recommended what the actuator does as a whole, and the actuator was shut surely.


TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A



ECN No: ECN-1610012

PAGE: **12** OF **15**



D. Lock release

Carefully rotate the actuator up to 90°, lifting it at the center.



TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN


RELEASE DATE: 2016/10/05

REVISION: A


ECN No: ECN-1610012

PAGE: **13** OF **15****Actuator operation**

Do not apply excessive force when opening the actuator . When opening make sure that the force is applied only to the actuator itself, avoiding touching of the contacts.



- The actuator opens by rotating it in the direction OPPOSITE to the direction of the insertion of the FPC. DO NOT attempt to open it from the same side as the insertion of the FPC.




TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **14** OF **15**



TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **15** OF **15****Precautions**


E. This connector is small and thin and requires delicate and careful handling.

Be very careful not to apply any force to the FPC after inserting it.

Otherwise, the connector may become unlocked or the FPC may break.

Fix the FPC, in particular, when loads are applied to it continuously.

Design the FPC layout with care not to bend it sharply near the insertion opening.



TITLE: 0.4 MM PITCH ZIF BACK-FLIP FPC CONN

RELEASE DATE: 2016/10/05

REVISION: A

ECN No: ECN-1610012

PAGE: **16** OF **15**

FPC Bending Direction

